



ToxCO[®]

Saving lives, one breath at a time.

Features and Benefits




For use with adults



To alert staff of high atmospheric CO



For use with unconscious patients



Tag Readings



Maintenance Reminders



Easy to use touchscreen interface

Ideal for:

- General practice
- Ambulance services
- Firemen
- First responders
- Health visitors



Technical Specification

Concentration range	0-54%COHb/0-600ppm
Display	Full colour touchscreen
Detection principle	Electrochemical sensor
Repeatability	≤±5% difference on consecutive readings
Accuracy	≤±3ppm/10% - whichever is greater*
Power	3 x AA (LR6 or equivalent) - up to 1000 minutes 1 x CR2032 lithium coin cell
T ₉₀ response time	<30 seconds
Operating temperature	0-50°C
Storage/ transport temperature	0-50°C
Operating/storage/transport pressure	Atmospheric ±10%
Operating humidity	15-90% non-condensing
Storage/transport humidity	0-95%
Sensor operating life	2 years
Sensor sensitivity	1ppm
Sensor drift	<5% per annum
Dimensions	Approx. 37 x 77 x 140mm
Weight	Approx. 215g (including batteries)
Materials	Case: polycarbonate/ABS blend with SteriTouch® anti-microbial additive D-piece™: polypropylene SteriBreath™: polypropylene OneBreath™: polypropylene
H ₂ cross interference	≤6%

*Readings of >500ppm at temperatures between 0-14°C can decrease accuracy to ≤±3ppm/15%.



Bedfont® Scientific Ltd.
Station Road, Harrietsham, Maidstone,
Kent, ME17 1JA England
Tel: +44 (0)1622 851122 Fax: +44 (0)1622 854860
Email: ask@bedfont.com Web: www.bedfont.com



Bedfont® GmbH
Mitterbachweg 18, 5081, Anif, Austria
Tel: +43 662 635050
Fax: +43 662 635050-50
Email: bedfont-gmbh@bedfont.com

©Bedfont® Scientific Limited 2021

Issue 9 - April 2021, Part No: MKT376
Bedfont® Scientific Limited reserves the right to change or update his literature without prior notice.
Registered in: England and Wales. Registered No: 1289798

